

RITIVEX R LIQUID 1102

ACRYLIC, ADHESIVE RESIN FOR MULTIPLE USES

GENERAL CHARACTERISTICS

- Acrylic, adhesive, joining resin, water - based.
- It is the suitable primer before the application of **ELASTOSPORT 853**, **ELASTOTURF 851** and **CORRIDOL 864** on athletic courts.
- It is used mainly as primer on asphalt and as primer for joining old and new concrete and as a primer on surfaces, before over coating them with concrete paints, emulsion paints, or cementitious coatings.
- **RITIVEX R LIQUID 1102** is applied in thin films.

TECHNICAL DATA

Appearance:	Water emulsion
Colors:	White
Density:	1.0-1.1 kg/lt at 25 °C
Viscosity:	15-45 mPa sec at 25°C
Temperature for the application and drying of the material:	10 – 40°C

CONSUMPTION

200-400 gr/m² depending on the type, roughness and absorbency of the underlay.

APPLICATION TOOLS

Roller, squeegee, brush or airless sprayer.



PACKAGING

Supplied in barrels of 200kg and drums of 20kg.

KDF - Kataskeves Dapedon LTD
e : exports@kdf.gr w : www.kdf.gr

Showroom Office
1 Papanikolaou Ave, Pefka
57010, Thessaloniki, Greece
t / f : 0030 2310 829598
Accounting Office
19 Mitropoleos Str
54624, Thessaloniki, Greece





STORAGE

One year in unopened containers in cool and dry places, out of sunlight, with minimum temperature 5°C and maximum temperature 30°C.

CAUTION

The application must take place in well-aired places using protective gloves. Skin or eye contact must be avoided, otherwise wash carefully with soap and water.

For more information consult the safety data sheet.

The information given here is true, represents our best knowledge and is based not only on laboratory work, but also on field experience. However, because of numerous factors affecting results we offer this information without any guarantee and no patent liability is assumed. For additional information or questions, contact the technical department of KDF LTD.